



	Fresh Water	Pool Water	Sea Water	220-240 V	400 V	110-120 V	50 Hz	60 Hz	12 V AC	24 V DC	DMX	DMX/RDM	Plug and Spray
ProfiPlane LED 110	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

## PROFIPLANE LED 110/DMX/02

The ProfiPlane LED 110/DMX/02, with 213 lumen and a beam angle of 25°, is the new, tiny, compact and powerful RGB-LED light for ground installation and wall mounting.

The cover glass is embedded in the stainless steel mounting ring forming a smooth surface. This makes it free from any extra dirt collecting edges. The compact LED-light (Ø = 109 mm) has a high quality stainless steel housing and is suitable for fresh water, pool water and sea water application (for definition see page 246). Equipped with a temperature control and a thermal protection, the LED light can also be installed dry. The lifetime of these lights is up to 100,000 h.\*

The RGB-LED light has a 1 mtr. long connecting cable with a hybrid (power/data) connector. The ProfiPlane LED light can be controlled via DMX with the underwater LED Driver/DMX/02 (50720) (not in scope of supply). The basic colours

of the LED-RGB-lights are measured individually for their brightness. The LED-Driver ensures equal brightness for all lights in the system, thereby creating a homogeneous colour combination.

### Product characteristics at a glance

- Energy efficient LED-RGB-light with stainless steel frame for wall mounting and ground installation
- Mounting ring and glass together form a plane surface
- 213 Lumen with a beam angle of 25°, max. 6 Watt
- Temperature controlled high quality LED for an extra-long life of up to 100,000 h.\*
- Wet and dry installation – water proof in accordance with IP68
- For fresh water, pool water and sea water
- External electronic in a separate control box / junction box – waterproof connector, easy to connect.
- DMX/RDM-capable in combination with the Underwater LED Driver/DMX/02 (50720)
- Individual measurement of the basic colours and the use of the Underwater LED Driver/DMX/02 (50720) guarantees equal brightness of all lights in the system and a homogeneous colour combination.
- Galvanic isolation between the DMX and 24V DC power
- Stroboscope effect, synchronised via DMX

\*In case of underwater application, an intelligent heat management and quality LED enables a lifetime of up to 100.000 hrs. This claim does not entitle to a guarantee.




ProfiPlane LED 110/DMX/02

The variety of colour combinations and the stroboscope effect reveal their full effect in combination with dynamic water effects which can be generated, for eg. , with the Varionaut pumps. Together, they create completely new compositions on open spaces and in fountains.

The Underwater LED Driver/DMX/02 (see page 166) is required for a DMX/RDM-capable application of the ProfiPlane LED light (see page 126-129) . In addition a RDM-capable controller, like WECS II (WECS II 512, WECS II 1024 or WECS II 2048 , see page 174-182), is also needed.



The ProfiPlane-LED light has a 1 mtr. long connecting cable with a hybrid connector for connecting it to the Underwater LED Driver/DMX/02. A 3.0 mtr. or 7.5 mtr. hybrid extension cable per light can be used for extending the connection (see page 164). Up to 4 LEDs can be individually controlled with this external Underwater LED-Driver. The Underwater



**Accessories** (must be ordered separately)

<b>Extension cable hybrid / 3.0 m</b> (see page 164)	<b>50728</b>
<b>Extension cable hybrid / 7.5 m</b> (see page 164)	<b>56403</b>
<b>Hybrid connection box</b> (see page 164)	<b>56404</b>
<b>Underwater LED Driver</b> (see page 166)	<b>50720</b>
<b>Connecting cable DMX/01</b> (see page 162)	<b>Order no.</b>
Connecting cable DMX/1.0 m/01	<b>12368</b>
Connecting cable DMX/3.0 m/01	<b>12369</b>
Connecting cable DMX/5.0 m/01	<b>12371</b>
Connecting cable DMX/10.0 m/01	<b>12372</b>
Connecting cable DMX/20.0 m/01	<b>12373</b>
End Resistant for Bus-System DMX/01	<b>12007</b>
<b>Connecting cable 24V DC/01</b> (see page 160)	<b>Order no.</b>
Connecting cable 24V DC /1.0 m/01	<b>12762</b>
Connecting cable 24V DC /3.0 m/01	<b>12552</b>
Connecting cable 24V DC /7.5 m/01	<b>12553</b>
Connecting cable 24V DC /15.0 m/01	<b>11720</b>
<b>PowerBox 24 V DC / 01</b> (see page 160)	<b>50493</b>
<b>Underwater power supply 250 / 24 V / 01</b> (see page 170)	<b>50733</b>
<b>WECS II 512 / DMX/02</b> (see page 174)	<b>56491</b>
<b>WECS II 1024 / DMX/02</b> (see page 174)	<b>56492</b>
<b>WECS II 2048 / DMX/02</b> (see page 180)	<b>56507</b>

LED Driver/DMX/02 is equipped with two connection boxes – one for the power supply with 24V DC and the other one for a DMX/RDM-data cable. The special connection technology makes a watertight pluggable cabling possible. The use of the hybrid connection box can lead to an economic advantage of the system. The lights which are connected to the hybrid box always have the same colour. (see system diagram.)



DMX-Channel	Function
Channel 1	red
Channel 2	green
Channel 3	blue
Channel 4	strobe

ProfiPlane LED 110/DMX/02		
Luminous flux all on	[lm]	213
Luminous flux red	[lm]	64
Luminous flux green	[lm]	114
Luminous flux blue	[lm]	35
Beam angle	[°]	25 (± 2)
Strobe effect	[Hz]	0-25
Energy efficiency category		A
Weighted energy consumption [kWh/1000h]		6.6
Rated voltage	[V/DC]	24
Power consumption	[W]	6
Rated current	[A]	0.26
Dim frequency	[Hz]	2800
Power connection type		Hybrid plug
Cable length	[m]	1
Protection class		IP 68
Static load max.	[t]	1.5
Dimensions (Ø x h)	[mm]	109 x 50
Material		Stainless steel 1.4404 (AISI 316L)
Weight	[kg]	0.61
<b>Order no.</b>		<b>56298</b>