

Telescopic nozzle extension TE 10 K with Lava 36-10 K

LUNAQUA 3 SET 1

- Consisting of a LunAqua 3 spotlight and either 1x ground stake, wall / floor bracket, spotlight base, nozzle bracket, coloured lens set
- Either pleasant white light or colour accents through use of the coloured lenses
- With spray water resistant transformer

EXTENSIONS

FM-Master WLAN you can switch, regulate and dim with an

app for smart phones or tablets. Item no. 40243 (page 242)

• For variable extension of the nozzle height



TECHNICAL DATAS

		LunAqua 3 Set 1	
Dimensions (Ø x H)	mm	80 x 140	
Rated voltage (primary, secondary)		230 V / 50 Hz, 12 V / AC	
Power consumption light fixture		20 W	
Energy efficiency class - light fixture '1		В	
Power consumption set	W	25	
Protection class		IP 68, IP 44 (power unit)	
Cable length 12 V device	m	2.00 (Power unit) + 5.00	
Net weight	kg	1.82	
Guarantee * P. 310	Years	2	
Illuminant type		Halogen	
Light flux	lm	300	
Light colour		Warm-white	
Colour temperature	K	2700	
Half peak angle		10 - 40 Degrees	
Safety transformer		20 UNITS	
Item no. (GB-Version)		-	
Item no.		56903	









TECHNICAL DATAS

		Telescopic nozzle extension TE 5 K	Telescopic nozzle extension TE 10 K	
Connection	mm	13	25	
Connection		1/2"	1"	
Length	mm	200-300	280-510	
Description		For variable extension of the		
		nozzle height		
Item no. (GB-Version)		-		
Item no.		54277	52270	