

Schematic diagram: Connection possibilities with the OASE InScenio garden outlets



INSCENIO

Flexible & decorative power management

Cover in sandstone-effect

InScenio Rock cover in stone décor elegantly conceals the technical unit. (optional accessory)



Splash guard

For your safety the InScenio cover protects the electronic components from splashing water.



Main module

Example – InScenio FM-Master 3 offers four power outlets of which two can be switched on and off. One input offers permanent power and one a dim function.



Remote control

From a range of up to 80 metres all functions can be easily and conveniently activated.



- Clever power connection system for the complete garden
- Extremely easy and flexible installation no digging whatsoever
- Retroactive extension is conveniently possible at any time
- Year round use thanks to splashproof and strain relieved power outlets
- Ground stake guarantees secure anchoring in the ground

From InScenio FM-Master 1

- Remote control range of the FM-Master to max. 80 m if there is no transmission interference

PRODUCT DETAILS



Strain relief

Strain relieved outlets are specially protected against mechanical stress and perfect for safe, year round use



Splash guard

To be on the safe side: The InScenio cover protects the electronic parts from splashing water. In addition, with the optional InScenio Rock cover the InScenio can be ideally integrated in the garden world.



Spike

The ground stake for easy installation without digging and secure anchoring in the ground, is included in the scope of delivery.



Remote control

The remote control unit of the FM Master included in the scope of delivery, and of the FM-ProfiMaster, has a range of up to 80 m, (if there is no transmission interference).


Extras

Top product characteristics

- Flexible modular system
- Easy installation, can also be retroactively extended
- Protective cover protects against splashing water and mechanical stress

Accessories

InScenio Rock sand
Cover in rock effect suitable for all InScenio FM-Master housings.
Item no. 50417 (page 298)



TECHNICAL DATAS

| | | InScenio Dimmer | InScenio 230 | InScenio FM-Master 1 | InScenio FM-Master 2 | InScenio FM-Master 3 | InScenio FM-ProfiMaster |
|--|-------|---------------------|-----------------|----------------------|----------------------|----------------------|---------------------------|
| Dimensions (L x W x H) | mm | 80 x 60 x 130 | 215 x 155 x 295 | | | | |
| Rated voltage | | 220 - 240 V / 50 Hz | | | | | |
| Max. total load power | W | 300 | 3600 | | | | |
| Max. total load current | A | 1.3 | 16.0 | | | | |
| Net weight | kg | 0.20 | 1.40 | 1.50 | 1.70 | 1.80 | 1.90 |
| Guarantee ^{* P. 310} | Years | 2 | | | | | 3 |
| Hand-held transmitter / range max. | m | - | | 80.00 | | | |
| Power outlets, permanent | | - | 4 x 230 V | 2 x 220 - 240 V | 1 x 220 - 240 V | | - |
| Number of power outlets on/off, max 2000 W | | - | - | 2 x 220 - 240 V | 3 x 220 - 240 V | 2 x 220 - 240 V | |
| Power outlets, dimmable | | 1 x max. 30 - 300 W | - | | | 1 x max. 40 - 320 W | 1 x max. 1250 W* |
| Item no. (GB-Version) | | Not available in GB | | | | | 56473 Not available in GB |
| Item no. | | 51160 | 55433 | 54978 | 36310 | 36311 | 56886 |



^{*1} Only InScenio FM-ProfiMaster

^{*2} Except InScenio Dimmer

^{*3} Max. 1 pump connection