





LunAqua 2/12 V

LUNAQUA MICRO ECO SET / LUNAQUA 2 / PROFILUX / LUNAQUA 3 SOLO

TECHNICAL DATAS









	LunAqua Micro Eco Set	LunAqua 2 / 12 V	LunAqua 3 Solo	ProfiLux 100 E
Dimensions (Ø x H) m	m 12 x 64	74 x 92	80 x 110	160 x 135
Rated voltage	12 V / AC	12 V AC / 50 Hz / 24 V DC	12 V / AC	230 V / 50 Hz
Rated voltage (primary, secondary)	230 V / 50 Hz, 12 V / AC -			
Power consumption light fixture	7 W	20 W		100 W
Energy efficiency class - light fixture 1	В			D
Power consumption set	V 10	-		110
Protection class	IP 68, IP 20 (power unit)	IP (58	IP 68, IP 44 (power unit)
Power cable length	m 2.00	3.00	-	7.50
Net weight	g 0.60	0.62	0.44	4.64
Guarantee *P.310 Yea	2			
Illuminant type	Halogen			
Light flux	m 90	30	0	-
Light colour	Warm-white			
Colour temperature	2700			
Half peak angle	300 Degrees	10 - 40 Degrees		24 Degrees
Number of cable entries E	A -	2		1
Entry cable size	-	PG 11		PG 13.5
Transformer	Yes	No		Yes
Item no. (GB-Version)	Not available in GB		-	
Product characteristics	Small compact indoor fountain light Now extremely energy-efficient and as bright as 10 watt Perfect for small bubbling stones A hole diameter of just 13 mm is required in bubbling stones Suitable for use under water (protection class IP 68) Included in the set: Transformer and cable	Garden light for use underwater and above the water For connection to the UST 150 underwater transformer Custom light effects thanks to the adjustable beam angle With ground stake and adjustable mounting base	 Garden light for use above water and underwater in a new design Can be connected in series or parallel 2 cable outlets High quality PG couplings Incl. mounting element with adjusting unit and ground stake Incl. 20 W illuminant Other 35 W illuminants can be used 	steel spotlight Stainless steel bracket for simple and safe installation With quick coupling and 105 VA weatherproof transformer Only suitable for underwater operation!
Item no.	40290	54993	57141	56898













