Application examples: The right choice underwater and above the water: **LunAqua Terra LED**

LunAqua Terra LED

*Warm light recessed in the ground –
as a complete installation set*

- Extremely energy-efficient with just 0.25 W per light fixture
- Warm white LED light fixture, extremely energy efficient and long lasting
- Crafted in polished, high-quality stainless steel material
- Installation is particularly easy thanks to the stainless steel clip for fastening in the 40 mm bore opening
- Suitable for use underwater and above the water
- Easy extension through LunAqua Terra LED Solo is possible (delivered without power unit)

LunAqua Terra LED Set 6 / Set 3
- Included in the scope of delivery: 6x distributor and low-voltage plug transformer

PRODUCT DETAILS

Oase

Stainless Steel Watercourses
Can be combined with the OASE stainless steel watercourse elements. Simply insert into the illumination element and the stainless steel watercourse shells become radiant highlights (fastening accessories included in the scope of delivery of the illumination element).

Maximum drive-over weight 3 t
When properly installed, load bearing capacity for pedestrian and vehicular traffic up to 3 t Also suitable for yard and driveway.

Watertight, in accordance with IP 68 protection rating
Water ingress is not possible! Thanks to high-quality workmanship and protection class IP 68 for continuous safe operation underwater and above the water (IP 44 connection).

Extension cable
10 m extension cable available as an accessory and suitable for bulb and 6x connector (max. 2 x per strand)

Extras

Top product characteristics
• *Pleasant warm light out of the ground for perfect evening atmosphere*
• *Individual installation possibilities: In the garden above the water and underwater*
• *Easy installation*

Recommendation
Whether on the terrace, in the swim pond or in the ground - the LunAqua Terra LED is suitable for various areas of implementation in the garden or in driveways. Installation is incredibly easy: Route the cable, insert the light fixture in the 40 mm bore – a romantic evening atmosphere is provided!

Accessories

LunAqua Terra LED
Extension cable 10 m
Item no. 51057 (page 248)

Stainless steel watercourse
illumination
Item no. 50809 (page 294)

TECHNICAL DATAS

		LunAqua Terra LED Set 6	LunAqua Terra LED Set 3	LunAqua Terra LED Solo
Dimensions (Ø x H)	mm	45 x 15		
Rated voltage		-		12 V / AC
Rated voltage (primary, secondary)		230 V / 50 Hz, 12 V / AC		-
Power consumption light fixture		0.25 W		
Power consumption set	W	4	3	-
Protection class		IP 68, IP 44 (power unit)		IP 68
Power cable length	m	10.00		
Net weight	kg	2.18	1.30	0.30
Guarantee * P. 310	Years	2		
Illuminant type		LED		
Light flux	lm	14		
Light colour		Warm-white		
Colour temperature	K	3000		
Half peak angle		diffuse		
Item no. (GB-Version)		Not available in GB		
Item no.		50729	51043	51056

*page 310

2 YEARS | 12V | CE