

# AQUAMAX Eco CLASSIC



The powerful classic in a completely new design



- Uncompromisingly reliable, with high cleaning force, it pumps pond water and coarse debris particles, up to 8 mm in size, into a filter.
- The completely redesigned classic – the entry level series of filter and watercourse pumps from OASE
- A totally new form: thanks to organic design, it can be integrated in ponds and watercourses, almost invisibly
- Extremely economical: thanks to its energy efficient motor, the AquaMax Eco Classic saves power – and money – in operation
- Suitable for use on swim ponds and bathing ponds (inserted in an exterior pump chamber)
- Included in the scope of delivery: special hose adapter with threaded collar for different hose sizes

## START



### From AquaMax Eco Classic 3500

- »Environmental Function Control« (EFC by OASE) protects against dry run and blocking\*1

Matching filters and filter systems starting on page 18

	AquaMax Eco Classic 2500	AquaMax Eco Classic 3500	AquaMax Eco Classic 5500	AquaMax Eco Classic 8500	AquaMax Eco Classic 11500	AquaMax Eco Classic 14500	AquaMax Eco Classic 17500	
Dimensions (L x W x H)	mm	190 x 175 x 100	280 x 230 x 130					
Rated voltage		220 - 240 V / 50 Hz						
Power consumption	W	40	45	60	80	100	135	170
Guarantee (+ extended guarantee) *P.97	Years	-	3 + 2					
Max. flow rate	l/h	2400	3600	5300	8300	11000	13600	17400
Max. head height	m	2.00	2.20	2.80	3.20	3.30	3.40	3.70
Connection for hoses	mm (inch)	19/25/32/38 (¾", 1", 1 ¼", 1 ½")						
Filter intake surface	cm²	300	810					
Coarse debris displacement max.	mm	6	8					
Setup type		Underwater installation only		Can be setup underwater & dry				
Item no. (GB-Version)		51088	51094	51098	51100	51103	51109	56710
Item no.		51086	51092	51096	51099	51102	51104	56653