



## Extras

### Top product characteristics

- Remote controlled water feature with varying fountains and white LED illumination
- Easy installation thanks to »Plug'n Spray«
- Can be used in swim ponds thanks to 12 V technology

### Recommendation

Splash water can be minimised by selecting a pool with at least a 3 m diameter. The OASE water reservoir WR 100 can be extended with pond liner, for example.



Schematic diagram: Water Trio in a reservoir

# WATER TRIO

## Luminous fountains for modern garden design

- High quality water feature with three varying fountains, including LED lighting

### TECHNICAL DATAS

		Water Trio
Dimensions (L x W x H)	mm	430 x 300 x 240
Net weight	kg	8.84
Guarantee (+ request guarantee) * P.310	Years	2 + 1
Light colour		neutral white
Cable length 12 V device	m	2.50 (Power unit) + 8.00
Fountain height, max.	m	1.40
Jet diameter	mm	5
<b>12 V control box</b>		
Dimensions control unit: (L x W x H)	mm	215 x 180 x 305
Power consumption	W	40
Rated voltage, prim. (control system)	V	12
Hand-held transmitter / range max.	m	80.00
<b>Power unit</b>		
Dimensions transformer: (L x W x H)	mm	160 x 100 x 100
Rated voltage (primary, secondary)		230 V / 50 Hz, 12 V / DC
Item no. (GB-Version)		-
Item no.		50240

- »Plug'n Spray« principle: Immediately ready for use and easy connection
- Variations in fountain height (30 - 140 cm) and light intensity can be played back in permanently set programs
- The programs can be conveniently selected via remote control from a distance of up to 80 m
- Can be connected to a timer
- Flexible setup on a wide variety of substrates
- Robust floor plate protects against damage
- Easy maintenance
- Low energy consumption
- Safe, energy-efficient 12 V technology
- Can even be used in swim ponds
- Included in the scope of delivery: 3 pumps / nozzles, external control unit, transformer and cables



PRO

Page 310

