



	Fresh Water	Pool Water	Sea Water	220-240 V	400 V	110-120 V	50 Hz	60 Hz
Skimmer 250		$\bigcirc$	$\bigcirc$		$\bigcirc$	$\bigcirc$		$\bigcirc$
Skimmer 250 A		$\bigcirc$	$\bigcirc$	$\bigcirc$	$\bigcirc$		$\bigcirc$	-

## SKIMMER 250 / 250A

Skimmer 250 is a high-performance floating skimmer that keeps up to 250 m<sup>2</sup> of surface water clean. The floating skimmer is particularly



Skimmer 250

well suited for bodies of water with significant water level fluctuation, and it can be flexibly implemented where pollutants accumulate.

## Product characteristics at a glance

- Powerful suction cleaning of pond surfaces up to 250 m<sup>2</sup>
- Optimal adaptation to water level differences
- Special large inlet and powerful suction capacity for first-class skimming results
- Extremely long service life thanks to high-quality workmanship and stainless steel elements
- Large, 27 litre stainless steel pollutant collection basket
- Fastening material included in the scope of delivery

Skimmer		250			250 A
Dimensions (L x W x H)	[mm]	775 x 400 x 590	Dimensions (L x W x H)	[inch]	30.5 x 18.8 x 23.2
Skimmer opening width	[mm]	520	Skimmer opening width	[inch]	20.50
Basket size (L x W x H)	[mm]	510 x 310 x 190	Basket size (L x W x H)	[inch]	700 / 5.8
Filter basket volume	[I]	27.00	Filter basket volume	[gal]	7.1
Rated voltage	[V/Hz]	220 - 240 / 50	Rated voltage	[V/Hz]	110 - 120 / 60
Power consumption (pump)	[W]	250	Power consumption (pump)	[W/A]	300 / 2.7
Litres per minute max.	[l/min]	250	Litres per minute max.	[gal/min]	66
Litres per hour max.	[l/h]	15000	Litres per hour max.	[gal/h]	3700
Pressure-side connection	[m]	1 1/2"	Pressure-side connection	[inch]	1½
Filter surface	[cm <sup>2</sup> ]	4500	Filter surface	[sq/ft.]	4.80
Suitable for ponds up to	[m <sup>2</sup> ]	250	Suitable for ponds up to	[sq/lbs.]	2690
Minimum water depth	[mm]	650	Minimum water depth	[inch]	2.60
Weight	[kg]	27.00	Weight	[lbs.]	64
Cable length	[m]	10.00	Cable length	[ft.]	7.50
Order no.		57480			57488

CLEANING & CARE