



OaseFol primer

Extras

Recommendation

Bonding of EPDM pond liner is a snap. High-quality material significantly facilitates handling: First apply the OaseFol Primer uniformly and let it flash-off, until a touch of the finger no longer pulls off threads of the primer. Then apply OaseFol SeamTape or the large repair tape OaseFol Flashing, to reliably bond seams and connections of OaseFol EPDM pond liner. The OASE pond construction case provides the necessary tools for processing EPDM liner.



OaseFol Bonding Adhesive

ACCESSORIES EPDM LINER/ACCESSORIES

Permanent, elastic bonding made easy

OASEFOL PRIMER



- Priming and activation for pre-treatment of EPDM liners prior to applying OaseFol SeamTape and flashing

		OaseFol Primer 0.75 l
Dimensions (L x W x H)	mm	100 x 100 x 120
Net weight	kg	0.70
Container size		0.75 l
Item no. (GB-Version)		-
Item no.		40000

OASEFOL BONDING ADHESIVE 5L



- Neoprene contact adhesive for bonding OaseFol to suitable substrates, such as metal, masonry and wood.

		OaseFol Bonding Adhesive 5 l
Dimensions (L x W x H)	mm	170 x 170 x 265
Net weight	kg	4.65
Container size		5 l
Item no. (GB-Version)		-
Item no.		57105

Tip!

Do you want to individually adapt the liner to the size and shape of your pond? No problem: Simply cut EPDM liner to size and connect the sections together. To do this, first apply OaseFol Primer, then tape and bond with OaseFol SeamTape. You will find EPDM liner processing videos at www.oase-livingwater.com