


ACCESSORIES – ILLUMINATION & POWER

REPLACEMENT BULBS

		Item no.	Item no. (GB-Version)	Power consumption	Energy efficiency class - light fixture ¹	Rated voltage	Description
	Halogen bulb 5 W	52662	–	5	C	12	• Underwater and above water implementation
	Halogen bulb 20 W	70703	–	20			
	Halogen bulb 35 W	54035	–	35			
	Halogen bulb 50 W	54036	–	50	D		• Can only be implemented underwater
	Halogen bulb 75 W	54037	–	75			

LUNAQUA TERRA LED CONNECTION TECHNOLOGY



LunAqua Terra LED extension cable 10 m

Power cable length	m	10.00
Cable cross section	mm ²	0.25
Rated voltage		12 V / AC
Protection class		IP 44
Net weight	kg	0.20
Guarantee ^{*P.310}	Years	2
Product characteristics	<ul style="list-style-type: none"> • 10 m extension cable (IP 44) for the LunAqua Terra LED in-ground light fixture • Suitable for bulb and 6x connector • Connection of a max. 2 extension cables per strand is possible 	
Item no. (GB-Version)	Not available in GB	
Item no.	51057	

LUNAQUA POWER LED CONNECTION TECHNOLOGY



LunAqua Power LED cable 10 m

Power cable length	m	10.00
Cable cross section	mm ²	0.34
Rated voltage		0 - 24 V / 350 mA / DC / 700 mA / DC
Protection class		IP 68
Net weight	kg	0.70
Guarantee (+ request guarantee) ^{*P.310}	Years	2 + 1
Product characteristics	<ul style="list-style-type: none"> • 10 m extension cable for the spotlight LunAqua Power LED • Suitable for extending the cable between spotlights and driver (max. 4x per strand) • All-round watertight to 4 m water depth 	
Item no. (GB-Version)	–	
Item no.	42636	

PROFILUX GARDEN LED RGB CONNECTION TECHNOLOGY



NEW



NEW

ProfiLux Garden LED controller

ProfiLux Garden LED cable 7.5 m

Dimensions (L x W x H)	mm	210 x 109 x 69	–
Rated voltage		–	24 V / DC
Rated voltage (primary, secondary)		230 V / 50 Hz, 24 V / DC	–
Power consumption	W	30	–
Number of cable entries	EA	1	–
Number of cable outlets	EA	4	–
Power cable length	m	5.00	7.50
Cable cross section	mm ²	–	0.25
Protection class		IP 68	
Net weight	kg	1.40	0.50
Guarantee (+ request guarantee) ^{*P.310}	Years	2 + 1	
Connection EGC		Yes	–
Product characteristics	<ul style="list-style-type: none"> • Robust underwater controller for control and power supply of the ProfiLux Garden LED RGB spotlight • Enables connection of up to 4 spotlights • Easy and safe operation above water and underwater – standard regulations do not allow use in swim ponds • All-round watertight to 4 m water depth 		
Item no. (GB-Version)			
Item no.	42639		42640

¹ Additional instructions concerning the energy efficiency classes are provided on page 302

LUNAQUA 10 CONNECTION TECHNOLOGY



	Underwater transformer UST 150 / 01	Connection cable 2.5 m / 01	Connection cable 5.0 m / 01	Connection cable 7.5 m / 01	PowerBox 12 V AC / 01	
Dimensions (L x W x H)	mm	154 x 130 x 89	-			75 x 80 x 95
Rated voltage		-	12 V / AC			
Rated voltage (primary, secondary)		230 V / 50 Hz, 12 V / AC	-			
Power consumption	W	150	-			
Number of cable entries	EA	1	-			
Number of cable outlets	EA	4	-			
Power cable length	m	10.00	2.50	5.00	7.50	
Cable cross section	mm ²	-	1.5		2.5	
Protection class		IP 68				
Net weight	kg	4.46	0.30	0.60	1.20	
Guarantee * P. 310	Years	2				
Product characteristics		<ul style="list-style-type: none"> • Connection possibility for up to 4 EA spotlights: 4 x 35 W, 3 x 50 W, 2 x 75 W halogen or 4 x 10 W LED spotlight • Robust underwater transformer for the LunAqua 10 system • Safe connection and operation of the light fixtures underwater • All-round watertight to 4 m water depth • Standard regulations do not allow underwater use of the UST 150 transformer in the swim pond. 	<ul style="list-style-type: none"> • Robust cable for connecting underwater transformer and spotlight in the LunAqua 10 system • Safe connection and operation of the light fixtures underwater • All-round watertight to 4 m water depth • Maximum cable length should not exceed a total of 60 m per strand • Longer connecting cable with larger cable cross-section is provided in the Commercial Catalogue 	<ul style="list-style-type: none"> • With the OASE PowerBox up to 12 LunAqua 10 LED spotlights can be connected on one UST 150 / 01 (up to 8 units in series) • All-round watertight to 4 m water depth • Safe connection and operation of the light fixtures underwater 		
Item no. (GB-Version)		-				
Item no.		50401	50402	50403	50404	

EGC CONNECTION TECHNOLOGY



NEW

	Connection Cable EGC 2.5 m	Connection Cable EGC 5.0 m	Connection Cable EGC 10.0 m	Cable connector EGC
Power cable length	m	2.50	5.00	10.00
Cable cross section	mm ²	0.22		
Protection class		IP 68		
Net weight	kg	0.39	0.69	1.29
Guarantee * P. 310	Years	2		
Product characteristics		<ul style="list-style-type: none"> • Special cable suitable for underwater use for bi-directional communication, e.g. between pumps, filters and control devices • 4-wire, shielded cable with a plug-and-socket connection 		
Item no. (GB-Version)		-		
Item no.		47038	47039	47040