



Extras

Top product characteristics

- Powerful suction cleaning of pond surfaces up to 50 m²
- Easy accessibility at the edge of the pond
- Rock look cover fits perfectly in the pond landscape

Recommendation

For the best possible result, surface skimmers should be installed on the side of the pond that is away from the wind.

BIO SYS SKIMMER +

Skimmer for installation on the pond edge

- Powerful suction cleaning of pond surfaces up to 50 m²
- Permanent installation directly at the edge of the pond
- Easy installation through joining the unit onto the pond liner
- Convenient cleaning thanks to easy removal of the coarse debris
- Compensation of water level fluctuations up to 100 mm
- For operation with AquaMax Eco in integrated pump chamber
- Included in the scope of delivery: Cover in natural rock look

TECHNICAL DATAS

		BioSys Skimmer +
Dimensions (L x W x H)	mm	580 x 400 x 450
Net weight	kg	5.32
Guarantee (+ request guarantee) * P.310	Years	3 + 2
Pos. water level difference		100 mm
Skimmer opening width	mm	220
Filter volume	l	12.0
Pond surface, max.	m ²	50
Pump capacity, min.	l/h	6000
Pump capacity, max.	l/h	16000
Connections, outlet	mm	25 / 32 / 38
Connections, outlet		1", 1 ¼", 1 ½"
Item no. (GB-Version)		-
Item no.		57137



Page 310

