



LUNAQUA 10 HALOGEN

Powerful halogen spotlight for every application

- Particularly powerful halogen spotlight with luminous intensity of up to 1,250 lumen
- Suitable for use underwater and above the water
- Suitable for permanent underwater use, thanks to protection class IP 68
- Available as spotlight without bulb
- Flexible extension and seamlessly compatible with the existing LunAqua 10 spotlights
- Pivot range approximately 180° thanks to the integrated mounting bracket
- Underwater transformer, bulbs and connecting cable available as accessories
- Easy installation



LunAqua 35 Set

- Included in the scope of delivery: Halogen spotlight including 35 W bulb, transformer and 7.5 m cable


Illumination Set Pond Jet:

- Perfect match for the OASE Pond Jet Floating Fountain
- Included in scope of delivery: 3x LunAqua 10 Halogen with 50 W Halogen illuminant, 3x holding bracket, 1x Underwater transformer UST 150 including stainless steel holder, 20 m cable

PRODUCT DETAILS



IP68 connection technology
All connection cables, transformers, and power supply can be operated constantly up to 4m under water!



Connection possibilities
For up to 4 spotlights, for example with 4 x 35 W, 3 x 50 W or 2 x 75 W halogen bulbs.



Sets
Available as a practical 35 W complete set and illumination set for the PondJet Eco floating fountain.

Extras

Top product characteristics

- Particularly powerful halogen spotlight with luminous intensity of up to 1,250 lumen
- Suitable for use underwater and above the water surface (to 4 m water depth)
- Flexible extension and seamlessly compatible with the LunAqua 10 spotlights

Recommendation

The cable cross section of the connecting cable that must be used is 2.5 mm² and the maximum cable length should not exceed 60 m per line overall.

TECHNICAL DATAS

		LunAqua 10	LunAqua 35 Set	Illumination set PondJet
Dimensions (L x W x H)	mm	145 x 160 x 182		
Rated voltage		12 V / AC	-	
Rated voltage (primary, secondary)		-	230 V / 50 Hz, 12 V / AC	
Power consumption light fixture		-	35 W	50 W
Energy efficiency class - light fixture ¹		-	B	
Power consumption set	W	-	46	157
Protection class		IP 68	IP 68, IP 44 (power unit)	IP 68
Cable length 12 V device	m	-	2.00 (Power unit) + 7.50	20.00 (Power unit) + 0.80
Net weight	kg	0.82	2.52	9.34
Guarantee * P. 310	Years	2		
Illuminant type		Halogen		
Light flux	lm	-	500	750
Light colour		Warm-white		
Colour temperature	K	2700		
Half peak angle		24 Degrees		
Cable cross section	mm ²	-	1.5	2.5
Item no. (GB-Version)		-		
Item no.		54034	54314	57083



¹ Additional instructions concerning the energy efficiency classes are provided on 302

Accessories

Underwater transformer UST 150 / 01

Easy and safe operation above water and underwater – standard regulations do not allow use in swim ponds
Item no. 50401 (page 249)



Connection cable 2.5 m / 01
Item no. 50402 (page 249)

Connection cable 5.0 m / 01
Item no. 50403 (page 249)

Connection cable 7.5 m / 01
Item no. 50404 (page 249)

Halogen bulb 35 W
Item no. 54035 (page 248)

Halogen bulb 50 W
Item no. 54036 (page 248)

Halogen bulb 75 W
Item no. 54037 (page 248)

