

PondoVac 3

Convenient and effective – without any disturbing interruptions whatsoever



- Vacuum non stop thanks to the patented two chamber system simultaneous vacuuming and emptying of the tank
- Maximum suction depth of 2.1 m thanks to strong 1600 W motor
- Can be used for cleaning garden ponds, pools and swim ponds as well as a wet vacuum in the household
- Transparent suction tube for flow through control
- Easy to move with transport rollers and adjustable handle
- Suction capacity up to 4,000 l/h, depending on the implementation conditions
- Included in the scope of delivery: 4 suction tubes (plastic), string algae nozzle, wet suction nozzle, universal nozzle, debris collection bag, 4 m long suction hose and 2.5 m long discharge hose

Two chamber system

Two same size cylinders are filled and emptied in alternating cycles. This enables non stop vacuuming.



Top product characteristics

- Continuous vacuum thanks to patented two chamber system
- Maximum suction depth of 2.1 m
- Also ideal for cleaning pools and swim ponds

Included in the scope of delivery

Universal nozzle The all round product (2–10 mm) removes pond floor debris without vacuuming up the gravel.

Special string algae nozzle With this nozzle, strands of string algae can be separated and easily removed.





Crevice nozzle Pollutants between stones and plants can be suctioned out with ease.

Wet suction nozzle Wet suction for indoors and outdoors.

Wastewater discharge Simply dispose of it as »organic fertiliser« in a flower bed or the sewer.

Accessories

Extension discharge set PondoVac 2.5 m hose with connection union and collection bag for coarse debris particles. Not suitable for pond silt!

Item no. 55448



PRODUCT DETAILS



Wastewater discharge Simply dispose of it as »organic fertiliser« in a flower bed or the sewer.

Handle, transport rollers + suction tube receptacle

Fast and convenient transport to the pond site via the adjustable and ergonomic handle.



Debris collection bag

Ideal for returning cleaned water when suctioning larger particles > 1 mm (not suitable for pond silt).

TECHNICAL DATAS

		PondoVac 3
Dimensions (L x W x H)	mm	380 x 380 x 685
Rated voltage		230 V / 50 Hz
Power consumption	W	1600
Power cable length	m	4.00
Net weight	kg	12.62
Guarantee (+ request guarantee) * P. 310	Years	2 + 1
Suction depth max.	m	2.10
Max. flow rate	l/h	4000
Length, suction hose	m	4.00
Length, discharge hose	m	2.50
Floating hose application		Not possible
Item no. (GB-Version)		-
Item no.		37102







