



Schematic diagram: ProfiSkim 100 in use

Extras

Top product characteristics

- Powerful suction cleaning of pond surfaces up to 80 m²
- Can be used with large filter systems and shallow water zones
- Perfect dimensions for large quantities of water

Recommendation

Ensure that the skimmer is installed in a horizontal position and confirm this with a spirit level. Place the skimmer in such a manner that you can execute maintenance tasks, such as emptying the basket.

PROFISKIM

The pro for the shallow water zone

- Powerful suction cleaning of pond surfaces up to 80 m²
- Ideal implementation in shallow water zones
- Can be used in gravity-fed operation (DN 110) or pump-fed operation, incl. 2" (50 mm) adapter
- Water routing for effective suction capacity
- Perfect supplement for filter systems in the gravity fed, as well as the pump fed system
- Large, easy to clean stainless steel basket with 8 mm mesh width
- Powerful suction cleaning of pond surfaces
- **ProfiSkim 100**
- Very amphibian-friendly, thanks to low flow speed at the overflow edge

TECHNICAL DATAS



		ProfiSkim 100	ProfiSkim Premium
Dimensions (L x W)	mm	780 x 585	500 x 340
Net weight	kg	13.06	9.10
Guarantee (+ request guarantee) * P.310	Years	3 + 2	
Height adaptation		350 - 550 mm	
Connections, outlet	mm	50	
Connections, outlet		2", DN 110	
Rec. flow rate (pump-fed)	l/h	10000-20000	6000-16000
Rec. flow rate (gravity-fed)	l/h	10000-12000	6000-12000
Filter volume	l	12.0	7.0
Pond surface, max.	m ²	80	65
Item no. (GB-Version)		-	
Item no.		57134	51185

*page 310

¹ ProfiSkim Premium² ProfiSkim 100